

ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of PREMIUM SERIE YS9035AJ

Product	Product Category	Coating
PTFE GLASS FABRIC	PREMIUM SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1500, 2000, 2600 mm	39.5, 59.1, 78.8, 102.4 inches
Thickness	0.35 mm	0.0138 inches
Coated weight	680 g/m ²	20 oz/yd ²
PTFE content	62%	62%
Tensile Stength	540 N/cm Warp	176 lbs/inches Warp
	508 N/cm Fill	290 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® offering PTFE fabric with easy release and high glossy coating, which also has super abrasion resistance, high mechanical strength and long lifetime.

0.35mm Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.

It is also widely used as a releasing sheet and laminating sheet for solar cell manufacturing, PVC or PE mold release, garment fusing, conveyor belt for paper industry, release & transport sheet for wood laminating, belting for food like Tortilla and so on.



ESONE® is a registered trademark owned by
 Jiangsu Esone New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-8759020 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com